

Automotive / LTV

DURACELL®

— ⊕ TRUSTED EVERYWHERE ⊖ —

High Performance • Trusted Starting Power



Duracell automotive batteries offer a complete, powerful line of maintenance-free products for cars, light trucks, and SUVs that has a name synonymous with the dependability and performance people know and trust.

The most advanced computerized equipment, stringent quality testing, finest raw material components, and special design features have been incorporated throughout the entire battery design to deliver maximum reliability, longevity, and cranking performance.

Whether pulling out the driveway or traveling thousands of miles from home, Duracell batteries deliver trusted starting power with every turn of the key. Help power more vehicles with the confidence of one of the world's most recognizable and trusted brands.

Duracell Automotive/LTV Batteries

GROUP NO.	PART NO.	PERFORMANCE LEVEL			FREE REPLACEMENT WARRANTY	APPROX. WEIGHT (lbs.)	MAXIMUM OVERALL DIMENSIONS						FOOTNOTES
		CCA @ 0°F	RES. CAP.	REF. CA			Length		Width		Height		
							inch	mm	inch	mm	inch	mm	
12-VOLT DURACELL® AUTO/LTV HP TECHNOLOGY													
24	HP24	675	115	850	24 MONTHS	40	10 3/4	273	6 3/4	171	9	229	6,17,22,45
24F	HP24F	675	115	850	24 MONTHS	40	10 3/4	273	6 3/4	171	9	229	6,17,22,45
27	HP27	710	120	860	24 MONTHS	45.5	12	305	6 3/4	171	9	229	6,21,45
27F	HP27F	710	120	860	24 MONTHS	45.5	12 3/4	314	6 3/4	171	9	229	6,21,45
34	HP34	690	110	820	24 MONTHS	36.5	10 3/4	273	6 3/4	175	8	203	6,17,18,22,37,45
34R	HP34R	690	110	820	24 MONTHS	36.5	10 3/4	273	6 3/4	175	8	203	6,17,18,22,37,45
36R	HP36R	650	120	800	24 MONTHS	42	10 1/4	260	7 1/4	184	8	203	6,45
40R (T6)	HP40R	650	105	810	24 MONTHS	37	11	278	6 3/4	175	6 3/4	175	6,17,22,26,45
41	HP41	650	100	800	24 MONTHS	38	11 1/16	293	6 3/4	175	6 3/4	175	6,22,45
47 (H5)	HP47	600	95	750	24 MONTHS	37.5	9 9/16	242	6 3/4	175	7 1/2	190	6,17,22,26,45
48 (H6)	HP48	680	120	850	24 MONTHS	42	11	278	6 3/4	175	7 1/2	190	6,17,22,26,45
49 (H8)	HP49	900	185	1080	24 MONTHS	54.5	13 1/16	354	6 3/4	175	7 1/2	190	6,17,22,26,45
51R	HP51R	500	75	600	24 MONTHS	28.5	9 3/4	238	5	127	8 3/4	222	6,22,45
59	HP59	590	100	700	24 MONTHS	37	9 1/2	241	7 7/16	189	7 1/2	190	6,17,45
65	HP65	875	150	1035	24 MONTHS	46.5	12	305	7 3/4	187	7 3/4	194	6,17,22,45
75	HP75	650	85	800	24 MONTHS	33	9 3/4	248	7	178	7 3/4	184	6,17,22,45
78	HP78	690	110	820	24 MONTHS	36.5	10 3/4	273	6 3/4	175	7 3/4	184	6,17,22,45
79	HP79	840	140	1000	24 MONTHS	43	12 1/16	307	7 7/16	179	7 3/4	188	6,22,45
85	HP85	650	110	775	24 MONTHS	35.5	9	229	6 3/4	175	8 3/4	206	6,22,45
86	HP86	690	90	775	24 MONTHS	35	9	229	6 3/4	175	8 3/4	206	6,22,45
90 (T5)	HP90	600	90	745	24 MONTHS	32.5	9 9/16	242	6 3/4	175	6 3/4	175	6,17,22,26,45
91 (T6)	HP91	700	100	875	24 MONTHS	38.5	11	278	6 3/4	175	6 3/4	175	6,17,22,26,45
93 (T8)	HP93	800	130	960	24 MONTHS	46.5	13 1/16	354	6 3/4	175	6 3/4	175	6,17,22,45
94R (H7)	HP94R	765	135	910	24 MONTHS	47.5	12 7/16	315	6 3/4	175	7 1/2	190	6,17,22,26,45
96R	HP96R	600	90	745	24 MONTHS	32.5	9 9/16	242	6 3/4	175	6 3/4	175	6,17,22,26,45
101	HP101	650	110	810	24 MONTHS	36	10 1/4	260	7 7/16	179	6 1/16	170	6,17,22,26,45
124R	HP124R	670	100	810	24 MONTHS	38	10 1/4	260	6 3/4	175	8 3/4	212	6,22,45
75/86	HP75DT	690	90	820	24 MONTHS	35	9 3/4	248	7	178	8 3/4	206	6,14,16,17,18,22,37,45
34/78	HP78DT	850	115	1020	24 MONTHS	41	10 3/4	273	6 3/4	175	8	203	6,14,16,17,18,22,37,45
12-VOLT DURACELL® AUTO/LTV													
24	D24	550	90	650	18 MONTHS	36.5	10 3/4	274	6 3/4	171	9	229	6,17,22,45
24F	D24F	550	90	650	18 MONTHS	36.5	10 3/4	274	6 3/4	171	9	229	6,17,22,45
25	D25	550	90	675	18 MONTHS	33.5	9 3/4	248	6 3/4	175	8 3/4	225	6,17,22,45
26	D26	540	80	665	18 MONTHS	29.5	8 3/4	222	6 3/4	171	8	203	6,17,18,22,37,45
26R	D26R	540	80	665	18 MONTHS	29.5	8 3/4	222	6 3/4	171	8	203	6,17,18,22,37,45
34	D34	550	90	690	18 MONTHS	33.5	10 3/4	274	6 3/4	176	8	203	6,17,18,22,37,45
35	D35	550	90	675	18 MONTHS	33.5	9 3/4	248	6 3/4	175	8 3/4	225	6,17,22,45
42	D42	475	70	590	18 MONTHS	29	9 9/16	242	6 3/4	175	6 3/4	175	6,45
51	D51	450	70	560	18 MONTHS	28	9 3/4	238	5	127	8 3/4	222	6,22,45
51R	D51R	450	70	560	18 MONTHS	28	9 3/4	238	5	127	8 3/4	222	6,22,45
58	D58	580	85	725	18 MONTHS	31.5	10	254	7 3/4	184	7	178	6,17,22,45
58R	D58R	580	85	725	18 MONTHS	31.5	10	254	7 3/4	184	6 3/4	175	6,17,22,45
65	D65	675	130	890	18 MONTHS	41	12	305	7 3/4	187	7 3/4	194	6,17,22,45
75	D75	540	85	670	18 MONTHS	32	9 3/4	248	7	178	7 3/4	185	6,17,22,45
86	D86	540	85	675	18 MONTHS	32	9	229	6 3/4	175	8 3/4	206	6,22,45
121R	D121R	540	80	665	18 MONTHS	30	8 3/4	210	6 3/16	177	8 3/4	206	6,45
75/86	D75DT	650	85	800	18 MONTHS	33	9 3/4	248	7	178	8 3/4	206	6,14,16,17,18,22,37,45
34/78	D78DT	690	110	820	18 MONTHS	36.5	10 3/4	273	6 3/4	175	8	203	6,14,16,17,18,22,37,45

FOOTNOTES:

- All batteries have SAE automotive posts
- 6. Black cover / Black case
- 14. Centerline terminal posts
- 16. Dual terminal universal design
- 17. Includes handle
- 18. Includes top adapter
- 21. Anchor lock elements
- 22. Flush manifold vented cover
- 26. Venting elbow supplied
- 37. For height with adapter add 7/8" (22mm)
- 45. If battery is used in on-highway vehicles equipped with two-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, free warranty replacement period will be 6 months

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

www.DriveDURACELL.com

E.P.M. Form No. 1857 Rev. 10/12 © 2012 by EPM Printed in U.S.A.

DURACELL®

— **TRUS±ED EVERYWHERE®** —

©2012 Duracell. Duracell is a registered trademark of the Gillette Company, used under license. All rights reserved.