

DURACELL®



Automotive

Extra High Performance • Trusted Starting Power

Duracell automotive batteries offer a complete, powerful line of maintenance-free products for cars, light trucks, and SUVs that has a name synonymous with the dependability and performance people know and trust.

Duracell EHP (Extra High Performance)

batteries utilize special features within the battery to withstand all temperature conditions. Reinforced internal components and a special plate active formula are just some of the features used in EHP technology to make the battery deliver superior life and maintenance-free performance in any climate.

Duracell HP (High Performance)

line provides another premium quality battery choice that strategically integrates value with high performance to deliver maximum reliability, longevity, and cranking power.

TRUST IS POWER.

Visit www.driveduracell.com to see the entire line of battery solutions for any application need.



Duracell Automotive Batteries

GROUP NO.	PART NO.	PERFORMANCE LEVEL				AP-PROX. WEIGHT (LBS.)	MAXIMUM OVERALL DIMENSIONS						FOOTNOTES
		CCA @ 0°F	RES. CAP.	REF. CA	FREE REPLACEMENT WARRANTY		LENGTH		WIDTH		HEIGHT		
							INCH	MM	INCH	MM	INCH	MM	
12-VOLT DURACELL® EHP — EXTRA HIGH PERFORMANCE													
24F	EHP24F	725	120	890	36 MONTHS	42.5	10 3/4	273	6 3/4	171	9	229	17,22,45
34	EHP34	800	115	985	36 MONTHS	41	10 3/4	273	6 7/8	175	8	203	17,18,22,37,45
35	EHP35	640	95	785	36 MONTHS	37	9 3/4	248	6 7/8	175	8 7/8	225	17,22,45
48 (H6/L3)	EHP48	730	120	900	36 MONTHS	43	11	278	6 7/8	175	7 1/2	190	17,22,26,45
65	EHP65	750	140	925	36 MONTHS	44	12	305	7 3/8	187	7 5/8	194	17,22,45
75	EHP75	690	95	850	36 MONTHS	36	9 3/4	248	7	178	7 1/4	184	17,22,45
78	EHP78	800	115	985	36 MONTHS	41	10 3/4	273	6 7/8	175	7 1/4	184	17,22,45
12-VOLT DURACELL® AUTO/LTV HP TECHNOLOGY													
24	HP24	650	115	800	24 MONTHS	41	10 3/4	273	6 3/4	171	9	229	17,22,45
24F	HP24F	650	115	800	24 MONTHS	41	10 3/4	273	6 3/4	171	9	229	17,22,45
27	HP27	710	120	875	24 MONTHS	48.5	12	305	6 3/4	171	9	229	21,45
27F	HP27F	710	120	875	24 MONTHS	48.5	12 3/8	314	6 3/4	171	9	229	21,45
34	HP34	690	110	850	24 MONTHS	38	10 3/4	273	6 7/8	175	8	203	17,18,22,37,45
34R	HP34R	690	110	850	24 MONTHS	38	10 3/4	273	6 7/8	175	8	203	17,18,22,37,45
36R	HP36R	650	120	800	24 MONTHS	41.5	10 1/4	260	7 1/4	184	8	203	45
40R (T6/LB3)	HP40R	650	105	800	24 MONTHS	38	11	278	6 7/8	175	6 7/8	175	17,22,26,45
41	HP41	650	100	800	24 MONTHS	38	11 9/16	293	6 7/8	175	6 7/8	175	22,45
47 (H5/L2)	HP47	650	100	800	24 MONTHS	37	9 9/16	242	6 7/8	175	7 1/2	190	17,22,26,45
48 (H6/L3)	HP48	680	120	835	24 MONTHS	42.5	11	278	6 7/8	175	7 1/2	190	17,22,26,45
49 (H8/L5)	HP49	900	185	1105	24 MONTHS	52.5	13 15/16	354	6 7/8	175	7 1/2	190	17,22,26,45
51R	HP51R	500	75	615	24 MONTHS	30	9 3/8	238	5	127	8 3/4	222	22,45
59	HP59	590	100	725	24 MONTHS	38	9 1/2	241	7 7/16	189	7 1/2	190	17,45
65	HP65	850	150	1045	24 MONTHS	46.5	12	305	7 3/8	187	7 5/8	194	17,22,45
75	HP75	650	90	800	24 MONTHS	34.5	9 3/4	248	7	178	7 1/4	184	17,22,45
78	HP78	690	110	850	24 MONTHS	38	10 3/4	273	6 7/8	175	7 1/4	184	17,22,45
79	HP79	840	140	1035	24 MONTHS	43	12 1/16	307	7 1/16	179	7 3/8	188	22,45
85	HP85	650	110	800	24 MONTHS	35	9	229	6 7/8	175	8 1/8	206	22,45
86	HP86	690	95	850	24 MONTHS	35.5	9	229	6 7/8	175	8 1/8	206	22,45
90 (T5/LB2)	HP90	600	90	740	24 MONTHS	34	9 9/16	242	6 7/8	175	6 7/8	175	17,22,26,45
91 (T6/LB3)	HP91	700	100	860	24 MONTHS	39	11	278	6 7/8	175	6 7/8	175	17,22,26,45
93 (T8/LB5)	HP93	800	130	985	24 MONTHS	47.5	13 15/16	354	6 7/8	175	6 7/8	175	17,22,26,45
94R (H7/L4)	HP94R	790	140	970	24 MONTHS	47	12 7/16	315	6 7/8	175	7 1/2	190	17,22,26,45
95R (H9/L6)	HP95R	850	190	1045	24 MONTHS	61.5	15 1/2	394	6 7/8	175	7 1/2	190	17,22,26,45
96R	HP96R	600	90	740	24 MONTHS	34	9 9/16	242	6 7/8	175	6 7/8	175	17,22,45
101	HP101	650	110	800	24 MONTHS	36	10 1/4	260	7 1/16	179	6 11/16	170	22,45
124	HP124	700	100	860	24 MONTHS	39.5	10 1/4	260	6 7/8	175	8 3/8	212	22,45
124R	HP124R	700	100	860	24 MONTHS	39.5	10 1/4	260	6 7/8	175	8 3/8	212	22,45
34/78	HP78DT	800	115	985	24 MONTHS	42	10 3/4	273	6 7/8	175	8	203	14,16,17,18,22,37,45
75/86	HP75DT	690	95	850	24 MONTHS	36.5	9 3/4	248	7	178	8 1/8	206	14,16,17,18,22,37,45
12-VOLT DURACELL® AUTO/LTV													
24	D24	550	90	675	18 MONTHS	37	10 3/4	273	6 3/4	171	9	229	17,22,45
24F	D24F	550	90	675	18 MONTHS	37	10 3/4	273	6 3/4	171	9	229	17,22,45
25	D25	550	90	675	18 MONTHS	34	9 3/4	248	6 7/8	175	8 7/8	225	17,22,45
26	D26	540	80	665	18 MONTHS	31	8 3/4	222	6 3/4	171	8	203	17,18,22,37,45
26R	D26R	540	80	665	18 MONTHS	31	8 3/4	222	6 3/4	171	8	203	17,18,22,37,45
34	D34	550	90	675	18 MONTHS	35	10 3/4	274	6 7/8	175	8	203	17,18,22,37,45
35	D35	550	90	675	18 MONTHS	34	9 3/4	248	6 7/8	175	8 7/8	225	17,22,45
42	D42	475	70	585	18 MONTHS	30	9 9/16	242	6 7/8	175	6 7/8	175	45
51	D51	450	70	555	18 MONTHS	28.5	9 3/8	238	5	127	8 3/4	222	22,45
51R	D51R	450	70	555	18 MONTHS	28.5	9 3/8	238	5	127	8 3/4	222	22,45
58	D58	580	85	715	18 MONTHS	32.5	10	254	7 1/4	184	7	178	17,22,45
58R	D58R	580	85	715	18 MONTHS	32.5	10	254	7 1/4	184	6 7/8	175	17,22,45
65	D65	675	130	830	18 MONTHS	41.5	12	305	7 3/8	187	7 5/8	194	17,22,45
75	D75	540	85	665	18 MONTHS	33	9 3/4	248	7	178	7 1/4	185	17,22,45
86	D86	540	85	665	18 MONTHS	35.5	9	229	6 7/8	175	8 1/8	206	22,45
121R	D121R	550	80	675	18 MONTHS	32.5	8 1/4	210	6 15/16	177	8 1/8	206	22,45
34/78	D78DT	690	110	850	18 MONTHS	39	10 3/4	273	6 7/8	175	8	203	14,16,17,18,22,37,45
75/86	D75DT	650	90	800	18 MONTHS	35	9 3/4	248	7	178	8 1/8	206	14,16,17,18,22,37,45

FOOTNOTES

– All batteries have SAE automotive posts
 14. Centerline terminal posts
 16. Dual terminal universal design

17. Includes handle
 18. Includes top adapter
 21. Anchor lock elements
 22. Flush manifold vented cover

26. Venting elbow supplied
 37. Height with adapter add 7/8" (22mm)
 45. If battery is used in on-highway vehicles equipped with two-way radios (such as taxis, police, and

emergency vehicles), marine applications, off highway use, and other non-automotive usage, free warranty replacement period will be 6 months



East Penn Manufacturing Co. • Lyon Station, PA 19536-0147
 Phone: 610-682-6361 • Fax: 610-682-4781 • www.DriveDURACELL.com
 All data subject to change without notice. No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.